

P/N NAS1921M06S03W

Military-Fasteners.com

#### Description

Fastener Length: 11/32"

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1921M06S03W
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-233-4764
Schedule B:	7508.90.5000
ECCN:	9A991



# P/N NAS1921M06S03W Specifications

0.350 Inches Nominal
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.186 Inches Minimum And 0.190 Inches Maximum
Self-plugging Mechanically Locked Stem
0.349 Inches Minimum And 0.357 Inches Maximum
Serrated Stem-type W
0.126 Inches Minimum And 0.187 Inches Maximum
98.5 Degrees Minimum And 101.5 Degrees Maximum
Iron Alloy 660 Locking Ring
Iron Alloy 660 Stem
Nickel Alloy 400 Sleeve
Ams5737 Fed Spec Single Material Response Stem
Qq-n-281 Fed Spec Single Material Response Locking Ring
Qq-n-281 Fed Spec Single Material Response Sleeve
Cadmium Sleeve
Passivate Locking Ring
Passivate Stem
Qq-p-416 Fed Spec Single Treatment Response Sleeve
Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Qq-p-35 Fed Spec Single Treatment Response Stem
80205-nas1921 Professional/industrial Association Standard

## **How to Order**

Order this rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1921M06S03W</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.