

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1921M06S06W   |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5320-01-192-9346 |
| Schedule B:        | 7508.90.5000     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

# P/N NAS1921M06S06W Specifications

|                              |  |
|------------------------------|--|
| Fastener Length:             | 0.513 Inches Nominal   |
| Head Style:                  | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Head Height:                 | 0.072 Inches Minimum And 0.085 Inches Maximum                                  |
| Shank Diameter:              | 0.186 Inches Minimum And 0.190 Inches Maximum                                  |
| Shank Style:                 | Self-plugging Mechanically Locked Stem   |
| Head Major Diameter:         | 0.349 Inches Minimum And 0.357 Inches Maximum                                  |
| Expansion Device:            | Serrated Stem-type W   |
| Grip Length:                 | 0.313 Inches Minimum And 0.375 Inches Maximum                                  |
| Countersink Angle:           | 100.0 Degrees Nominal  |
| Material:                    | Nickel Sleeve  |
| Material:                    | Steel Locking Ring   |
| Supplementary Features:      | Used With Single Action Hand Or Automated Tool                                 |
| Specification/standard Data: | 80205-nas1921 Professional/industrial Association Standard                     |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M06S06W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.