

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M06S06W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-192-9346
Schedule B:	7508.90.5000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1921M06S06W Specifications

<b>Fastener Length:</b>	0.513 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.072 Inches Minimum And 0.085 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Nickel Sleeve
<b>Material:</b>	Steel Locking Ring
<b>Supplementary Features:</b>	Used With Single Action Hand Or Automated Tool
<b>Specification/standard Data:</b>	80205-nas1921 Professional/Industrial Association Standard

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M06S06W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.