

Description

Fastener Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1921M06S06WU |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-482-0315 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |



NO IMAGE
AVAILABLE

P/N NAS1921M06S06WU Specifications

| | |
|---|---|
| Identification Code Color: | Yellow |
| Fastener Length: | 0.946 Inches Nominal |
| Head Style: | Tapered Pan |
| Shank Style: | Straight |
| Expansion Device: | Break Stem |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 National Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,type 2, Class 3 National Spec All Treatment Responses Sleeve |

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M06S06WU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.