

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M06S07W
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-192-9345
Schedule B:	7508.90.5000
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1921M06S07W Specifications

Fastener Length:	0.576 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.072 Inches Minimum And 0.085 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Sleeve
Material:	Steel Locking Ring
Supplementary Features:	Used With Single Action Hand Or Automated Tool
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M06S07W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.