

P/N NAS1921M08S07

Description

Fastener Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1921M08S07

Minimum Qty (MOQ): 1 EA

NSN: 5320-01-240-8096

Schedule B: 7318.23.0000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N NAS1921M08S07 Specifications

0.647 Inches Nominal
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.155 Inches Minimum And 0.159 Inches Maximum
Self-plugging Mechanically Locked Stem
0.282 Inches Minimum And 0.290 Inches Maximum
Serrated Stem-type W
0.376 Inches Minimum And 0.437 Inches Maximum
1050 Pounds Per Square Inch
1565 Single Pounds Per Square Inch
98.5 Degrees Minimum And 101.5 Degrees Maximum
Single Action
Nickel Alloy Sleeve
Steel Corrosion Resisting Locking Ring Or Nickel Alloy Locking Ring
Steel Corrosion Resisting Stem
Ams5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Ams5737 Assn Std Single Material Response Stem
Qq-n-281 Fed Spec Single Material Response Sleeve
Cadmium Sleeve Or Aluminum Sleeve
Passivate Locking Ring
Passivate Stem
Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Qq-p-35 Fed Spec Single Treatment Response Stem
Qq-p-416,ty li,cl 3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve
80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1921M08S07 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.