

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M08S08
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-281-7196
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1921M08S08 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.710 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.472 Inches Minimum And 0.480 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Nominal Mills And 0.500 Nominal Centimeters
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Special Features:	Rivet To Be Used With Single Action Hand Held Installation Tools Or In Automated Installation Equipment
Material:	Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M08S08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.