

Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1953C5
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-548-2247
Schedule B:	7318.15.8085
ECCN:	9A991



P/N NAS1953C5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.635 Inches Minimum And 0.665 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1881 Inches Minimum And 0.1887 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	896 Megapascals
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	586 Megapascals
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall And Ams5732 Assn Std 2nd Material Response Overall And Ams5737 Assn Std 3rd Material Response Overall And Ams585 Assn Std 4th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1953C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.