

Description

Fastener Length: 2-7/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1954C32
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-464-3921
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1954C32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	2.410 Inches Minimum And 2.440 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	6980 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt, Shear, Hexagon Head, 108 Ksi Shear, Long Thread
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1954C32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.