

Description

Fastener Length: 7/8", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1954C7H |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-170-5557 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1954C7H Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.400 Inches Minimum And 0.450 Inches Maximum |
| Fastener Length: | 0.848 Inches Minimum And 0.875 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Hole Diameter: | 0.046 Inches Minimum And 0.056 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Corners |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1954 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1954C7H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.