

Description

Fastener Length: 3-7/16", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS195646 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-585-3096 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1956-46 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.578 Inches Nominal |
| Fastener Length: | 3.453 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.373 Inches Minimum And 0.374 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 2.865 Inches Minimum And 2.885 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Bolt Shear Hexagon Head 108 Ksi Shear Long Thread |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1956-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.