

P/N NAS1956-9

Description

Fastener Length: 1-9/64", Thread: 3/8-24, Thread Length: 19/32", NAS1956 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS19569

Minimum Qty (MOQ): 10

NSN: 5306-01-272-5160

Schedule B: 7318.15.2095

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS1956-9 Specifications

Thread Direction: Right-hand Thread Length: 0.553 Inches Minimum And 0.603 Inches Maximum Fastener Length: 1.125 Inches Minimum And 1.155 Inches Maximum Head Style: Dished Hexagon Head Height: 0.188 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.3745 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.3745 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Minimum And 0.572 Inches Maximum Width Between Flats: 0.552 Inches Max		
Thread Length: 0.553 Inches Minimum And 0.603 Inches Maximum Fastener Length: 1.125 Inches Minimum And 1.155 Inches Maximum Head Style: 0.188 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Width Between Flats: 0.3735 Inches Minimum And 0.3745 Inches Maximum Grip Diameter: 0.375 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Winimum Thread Diameter: 0.352 Inches Minimum And 0.572 Inches Maximum Thread Quantity Per Inch: 44 Winimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Waterial: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Will-s-5026 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Classification: Unif Whead Series Designator: Unif	Thread Class:	3a
Fastener Length: 1.125 Inches Minimum And 1.155 Inches Maximum Dished Hexagon Head Style: 0.188 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Minimum And 0.572 Inches Maximum Thread Diameter: 0.552 Inches Minimum And 0.572 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mili-s-5626 Mil Spec 1st Material Response Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Cadmium Overall And Chromate Overall Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Thread Direction:	Right-hand
Head Style: Head Height: 0.188 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.3745 Inches Maximum Scrip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Minimum And 0.372 Inches Maximum Thread Quantity Per Inch: 0.552 Inches Minimum And 0.572 Inches Maximum Thread Quantity Per Inch: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Classification: Unjf Unjf	Thread Length:	0.553 Inches Minimum And 0.603 Inches Maximum
Head Height: 0.188 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Grip Diameter: 0.375 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.552 Inches Minimum And 0.572 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec Surface Treatment: 0cq-9-416,type 2,class 2 Fed Spec Single Treatment Response Overall Classification: Thread Series Designator: Unjf	Fastener Length:	1.125 Inches Minimum And 1.155 Inches Maximum
Width Between Flats: O.553 Inches Minimum And O.564 Inches Maximum O.3735 Inches Minimum And O.3745 Inches Maximum O.3735 Inches Minimum And O.3745 Inches Maximum O.375 Inches O.375 Inches O.552 Inches Minimum And O.572 Inches Maximum Overall Stread Quantity Per Inch: O.552 Inches Minimum And O.572 Inches Maximum Overall And 43.0 Rockwell C Maximum Overall Overall C Maximum Overall Overall C Maximum Overall O	Head Style:	Dished Hexagon
Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum 0.375 Inches 0.375 Inches 0.375 Inches 0.552 Inches Minimum And 0.572 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Material: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Gardinum Overall And Chromate Overall Classification: Thread Series Designator: Unjf	Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.552 Inches Minimum And 0.572 Inches Maximum 24 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall 5urface Finish: 32.0 Microinches Bearing Surface Of Head 5urface Finish: 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads 5urface Finish: 5urface Finish: 5urface Finish: 5urface Treatment Document And Classification: 5urface Treatment Document And Classification: 5urface Treatment Document And Classification: Thread Series Designator: Unjf	Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Length: 0.552 Inches Minimum And 0.572 Inches Maximum 24 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Gurface Treatment Document And Classification: Gurface Treatment Document And Classification: Thread Series Designator: Unjf	Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Minimum Tensile Strength: 180000 Pounds Per Square Inch 180000 Pounds Per Square Inch 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall 50 Unface Finish: 50 Unface Finish: 50 Unface Finish: 51 Unface Finish: 52 Undicroinches Bearing Surface Of Head 53 Undicroinches Grip 54 Undicroinches Grip 55 Unface Finish: 55 Unface Finish: 56 Unface Finish: 57 Undicroinches Threads 58 Underial: 58 Underial: 58 Underial: 58 Underial: 59 Underial: 50	Nominal Thread Diameter:	0.375 Inches
Minimum Tensile Strength: Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads 32.0 Microinches Grip 32.0 Micro	Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Hardness Rating: 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Thread Quantity Per Inch:	24
Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall Unjf	Minimum Tensile Strength:	180000 Pounds Per Square Inch
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Gurface Treatment Document And Classification: Uq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall Unjf	Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Re	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Over	Surface Finish:	32.0 Microinches Threads
Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Classification: Classification: Classification: Oq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall Unjf	Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall Unjf	Material Document And Classification:	
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1956 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas1956 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS1956-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS1956-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS1956-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS1956-9 and selecting the quantity you want then click "add to cart".