

Description

Fastener Length: 23/32", Thread: 8-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1992C6T
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-286-2640
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



P/N NAS1992C6T Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.363 Inches Maximum
Fastener Length:	0.698 Inches Minimum And 0.728 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.253 Inches Minimum And 0.261 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1992 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1992C6T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.