

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1992T3T |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5305-01-545-5791 |
| ECCN: | EAR99 |

NAS1992T3T



P/N NAS1992T3T Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Nominal |
| Fastener Length: | 0.526 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.253 Inches Minimum And 0.261 Inches Maximum |
| Grip Diameter: | 0.162 Inches Minimum And 0.163 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.188 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4971 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1992 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1992T3T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.