

**Description**

Fastener Length: 9/16", Thread: 8-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1992T4T
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-545-5790

NO IMAGE  
AVAILABLE

## P/N NAS1992T4T Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.338 Inches Nominal
<b>Fastener Length:</b>	0.588 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.253 Inches Minimum And 0.261 Inches Maximum
<b>Grip Diameter:</b>	0.162 Inches Minimum And 0.163 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Grip Length:</b>	0.220 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams 4971 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1992 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1992T4T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.