

P/N NAS1993-3T

Description

length: 0.526", thread: 10-32, reduced head bolt - 100°, flat head - torq-set recess - alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS19933T

Minimum Qty (MOQ): 100

NSN: 5305-01-209-7204

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1993-3T Specifications

3a
Right-hand
0.313 Inches Minimum And 0.363 Inches Maximum
0.511 Inches Minimum And 0.541 Inches Maximum
Flat Countersunk
0.2516 Inches Minimum And 0.3047 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
Offset Cruciform (torque Set)
0.190 Inches
0.178 Inches Minimum And 0.198 Inches Maximum
32
39.0 Rockwell C Minimum And 43.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Cadmium And Chromate Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1993 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1993-3T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.