

P/N NAS1996-8T

Description

length: 1.078", thread: 3/8-24, reduced head bolt - 100°, flat head - torq-set recess - alloy steel

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS19968T

Minimum Qty (MOQ):

NSN: 5305-01-268-1207

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1996-8T Specifications

70
3a
Right-hand
0.553 Inches Minimum And 0.603 Inches Maximum
1.063 Inches Minimum And 1.093 Inches Maximum
Flat Countersunk
0.513 Inches Minimum And 0.566 Inches Maximum
0.3735 Inches Minimum And 0.3745 Inches Maximum
Offset Cruciform (torque Set)
0.375 Inches
0.490 Inches Minimum And 0.510 Inches Maximum
24
39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
32.0 Microinches Grip
32.0 Microinches Threads
63.0 Microinches Bearing Surface Of Head
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1996 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1996-8T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1996-8T and selecting the