

Description

Shear Bolt-lock part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS2006V06 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-00-303-1172 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N NAS2006V06 Specifications

| | |
|--|---|
| Head Style: | Straight Pan |
| Head Height: | 0.099 Inches Minimum And 0.111 Inches Maximum |
| Shank Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Grip Length: | 0.375 Inches Nominal |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall |
| Specification/standard Data: | 80205-nas2006 Professional/industrial Association Standard |

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2006V06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.