

Description

Shear Bolt-lock part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2006V07
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-050-6179
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2006V07 Specifications

Head Style:	Straight Pan
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Grip Length:	0.407 Inches Minimum And 0.469 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Chlorine Free Cetyl Alcohol Lubrication
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2006V07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.