

**Description**

Fastener Length: 5/8", Thread: 8-32, Thread Length: 31/64", NAS220 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS2209
Minimum Qty (MOQ):	100
NSN:	5305-00-271-8692
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS220-9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.346 Inches Minimum And 0.485 Inches Maximum
<b>Fastener Length:</b>	0.579 Inches Minimum And 0.626 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.309 Inches Minimum And 0.331 Inches Maximum
<b>Head Height:</b>	0.088 Inches Minimum And 0.102 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 8630
<b>Screw Material Document And Classification:</b>	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS220-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.