

P/N NAS221-11

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 33/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS27039-0811

SKU / Model: NAS22111

Minimum Qty (MOQ): 20

NSN: 5305-00-165-5359

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS221-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.377 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.704 Inches Minimum And 0.751 Inches Maximum
Head Style:	Round
Head Diameter:	0.361 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, C-18a, Ec-18b; Aircraft, T-2; Helicopter, Seahawk H-60; Submarine Armament And Fire Control Systems; F4s Aircraft; Missile, All-weather Anti-ship, Harpoon (agm-84); Consolidated Targets; Support Equipment, B-52 Aircraft; Joint Stars Target Radar System.
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS221-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.