

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 33/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS27039-1-13](#)

SKU / Model:	NAS22113
Minimum Qty (MOQ):	50
NSN:	5305-00-282-4204
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS221-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.377 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.829 Inches Minimum And 0.876 Inches Maximum
Head Style:	Round
Head Diameter:	0.361 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS221-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.