

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 33/64", NAS221 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS2219 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-282-4208 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS221-9 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.377 Inches Minimum And 0.516 Inches Maximum |
| Fastener Length: | 0.579 Inches Minimum And 0.626 Inches Maximum |
| Head Style: | Round |
| Head Diameter: | 0.361 Inches Minimum And 0.385 Inches Maximum |
| Head Height: | 0.103 Inches Minimum And 0.118 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 8630 |
| Screw Material Document And Classification: | Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS221-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.