



Military-Fasteners.com

P/N NAS223-30

Description

Fastener Length: 1-61/64", Thread: 1/4-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS22330
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-285-2623
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS223-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.465 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	1.907 Inches Minimum And 1.954 Inches Maximum
Head Style:	Round
Head Diameter:	0.568 Inches Minimum And 0.601 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.183 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS223-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.