

**Description**

Shear Bolt-lock part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2406V04A
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-046-2048
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS2406V04A Specifications

<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.056 Inches Minimum And 0.063 Inches Maximum
<b>Shank Diameter:</b>	0.2021 Inches Minimum And 0.2026 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.288 Inches Minimum And 0.302 Inches Maximum
<b>Grip Length:</b>	0.189 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas 621 Assn Std Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas2406 Professional/industrial Association Standard

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2406V04A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.