

Description

Shear Bolt-lock part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2406V04A
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-046-2048
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N NAS2406V04A Specifications

Head Style:	Straight Pan
Head Height:	0.056 Inches Minimum And 0.063 Inches Maximum
Shank Diameter:	0.2021 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.189 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2406 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2406V04A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.