

Description

Shear Bolt-lock part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS2406V05A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-046-2049 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N NAS2406V05A Specifications

| | |
|--|---|
| Head Style: | Straight Pan |
| Head Height: | 0.056 Inches Minimum And 0.063 Inches Maximum |
| Shank Diameter: | 0.2021 Inches Minimum And 0.2026 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.288 Inches Minimum And 0.302 Inches Maximum |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Assn Std Single Material Response Overall |
| Specification/standard Data: | 80205-nas2406 Professional/industrial Association Standard |

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2406V05A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.