

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2408V07
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-062-3611
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2408V07 Specifications

Fastener Length:	0.683 Inches Nominal
Head Style:	Err-090
Head Height:	0.074 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.363 Inches Minimum And 0.377 Inches Maximum
Grip Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall
Specification/standard Data:	80205-nas2408 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2408V07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.