

Description

Shear Bolt-lock part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2506V07A
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-045-0196
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS2506V07A Specifications

Head Style:	Flush Countersunk
Shank Diameter:	0.2021 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.305 Inches Maximum
Grip Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2506 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2506V07A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.