

Description

Fastener Length: "

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2508V08
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-310-7452
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2508V08 Specifications

Fastener Length:	0.746 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Shank Style:	Pin-riquet, Multiple Grooved
Head Major Diameter:	0.344 Inches Minimum And 0.399 Inches Maximum
Grip Length:	0.439 Inches Minimum And 0.500 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall
Specification/standard Data:	80205-nas2508 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2508V08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.