

Description

Fastener Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2605V02
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-298-6360
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

# P/N NAS2605V02 Specifications

Fastener Length:	0.363 Inches Maximum
Head Style:	Err-090
Head Height:	0.036 Inches Minimum And 0.048 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.235 Inches Minimum And 0.249 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2605 Professional/industrial Association Standard

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2605V02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.