

**Description**

Fastener Length: 47/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2605V08
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-298-6499
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS2605V08 Specifications

<b>Fastener Length:</b>	0.738 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.036 Inches Minimum And 0.048 Inches Maximum
<b>Shank Diameter:</b>	0.1630 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.235 Inches Minimum And 0.249 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.439 Inches Minimum And 0.500 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2605V08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.