

Description

Fastener Length: 1-5/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2606V14
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-266-3125
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

## P/N NAS2606V14 Specifications

<b>Fastener Length:</b>	1.069 Inches Minimum And 1.079 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.044 Inches Minimum And 0.056 Inches Maximum
<b>Shank Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.288 Inches Minimum And 0.302 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.813 Inches Minimum And 0.875 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4967 Assn Std Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas2606 Professional/industrial Association Standard

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2606V14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.