

Description

Fastener Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2606V14
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-266-3125
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2606V14 Specifications

Fastener Length:	1.069 Inches Minimum And 1.079 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.044 Inches Minimum And 0.056 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.288 Inches Minimum And 0.302 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.813 Inches Minimum And 0.875 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2606 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2606V14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.