

## **P/N NAS2608V07**

### **Description**

Bolt part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS2608V07

Minimum Qty (MOQ): 10 EA

NSN: 5320-00-303-1093

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS2608V07 Specifications**

Head Style:	Straight Pan
Head Height:	0.058 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.363 Inches Minimum And 0.377 Inches Maximum
Grip Length:	0.438 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall
Specification/standard Data:	80205-nas2608 Professional/industrial Association Standard

# **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS2608V07">https://military-fasteners.com/bolts/machine+bolts/NAS2608V07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.