

## Description

Shear Bolt-lock part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS2705V02
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-283-4871
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

# P/N NAS2705V02 Specifications

Head Style:	Flush Countersunk
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.220 Inches Minimum And 0.256 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	Ws: Aircraft, Eagle F-15; Aircraft, Harrier Av-8b; Aircraft, Hornet F/a -18
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	2900 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705V02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.