

**Description**

Shear Bolt-lock part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2705V02
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-283-4871
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS2705V02 Specifications

<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.1630 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.220 Inches Minimum And 0.256 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>End Item Identification:</b>	Ws: Aircraft, Eagle F-15; Aircraft, Harrier Av-8b; Aircraft, Hornet F/a -18
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	2900 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Criticality Code Justification:</b>	Feat
<b>Special Features:</b>	Weapon System Essential
<b>Material:</b>	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705V02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.