

Description

Fastener Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2705V05
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-281-8170
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS2705V05 Specifications

Fastener Length:	0.481 Inches Minimum And 0.551 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.220 Inches Minimum And 0.256 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	Wsd: Aircraft, Hornet F/a-18; Aircraft, Harrier Av-8b; Aircraft, Eagle F-15; F/a-18e/f Hornet Aircraft
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2705 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705V05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.