

Description

Fastener Length: 43/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2705V07
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-338-5848
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2705V07 Specifications

Fastener Length:	0.606 Inches Minimum And 0.676 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.220 Inches Minimum And 0.256 Inches Maximum
Grip Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2705 Professional/Industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705V07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.