

**Description**

Fastener Length: 25/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2705V09
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-338-5858
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS2705V09 Specifications

<b>Fastener Length:</b>	0.725 Inches Minimum And 0.795 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.163 Inches Minimum And 0.164 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.220 Inches Minimum And 0.256 Inches Maximum
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas 621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams 4928 Assn Std Single Material Response Overall

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705V09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.