

Description

Fastener Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2705V09
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-338-5858
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS2705V09 Specifications

Fastener Length:	0.725 Inches Minimum And 0.795 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.163 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.220 Inches Minimum And 0.256 Inches Maximum
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams 4928 Assn Std Single Material Response Overall

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705V09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.