

Description

Fastener Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2705VH03
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-059-7567
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N NAS2705VH03 Specifications

Fastener Length:	0.356 Inches Minimum And 0.426 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.256 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.188 Inches Maximum
Shear Strength:	4000 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Chlorine Free Cetyl Alcohol Lubrication
Material:	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas2705 Professional/industrial Association Standard

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705VH03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.