

Description

Fastener Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS2705VH03 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-059-7567 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2705VH03 Specifications

| | |
|--|---|
| Fastener Length: | 0.356 Inches Minimum And 0.426 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.1630 Inches Minimum And 0.1635 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.256 Inches Maximum |
| Grip Length: | 0.126 Inches Minimum And 0.188 Inches Maximum |
| Shear Strength: | 4000 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Chlorine Free Cetyl Alcohol Lubrication |
| Material: | Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Assn Std Single Material Response Overall |
| Specification/standard Data: | 80205-nas2705 Professional/industrial Association Standard |

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2705VH03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.