

**Description**

Fastener Length: 57/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2706V11
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-301-8628
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS2706V11 Specifications

<b>Fastener Length:</b>	0.882 Inches Minimum And 0.892 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.189 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.262 Inches Minimum And 0.305 Inches Maximum
<b>Grip Length:</b>	0.626 Inches Minimum And 0.688 Inches Maximum
<b>Minimum Yield Strength:</b>	120000 Pounds Per Square Inch
<b>Shear Strength:</b>	5380 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall
<b>Specification/standard Data:</b>	80205-nas2706 Professional/industrial Association Standard

## How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2706V11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.