

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS2708V03 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5320-00-303-1216 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS2708V03 Specifications

| | |
|--|---|
| Fastener Length: | 0.434 Inches Minimum And 0.504 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.344 Inches Minimum And 0.399 Inches Maximum |
| Grip Length: | 0.126 Inches Minimum And 0.188 Inches Maximum |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Uns R54520 Overall Or Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall |
| Specification/standard Data: | 80205-nas2708 Professional/industrial Association Standard |

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2708V03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.