

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS2708V04 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-307-2322 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS2708V04 Specifications

| | |
|--|---|
| Fastener Length: | 0.501 Inches Nominal |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.344 Inches Minimum And 0.399 Inches Maximum |
| Grip Length: | 0.189 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Nas 621 Comp 6al-4v Assn Std Single Material Response Overall |
| Specification/standard Data: | 80205-nas2508 Professional/industrial Association Standard |

How to Order

Order this shear bolt-lock from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2708V04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.