

**Description**

Fastener Length: 1-7/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS280314        |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5305-01-308-2902 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N NAS2803-14 Specifications

|                                                       |                                                                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                                                   |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                                           |
| <b>Thread Length:</b>                                 | 0.313 Inches Minimum And 0.363 Inches Maximum                                                                                        |
| <b>Fastener Length:</b>                               | 1.198 Inches Minimum And 1.228 Inches Maximum                                                                                        |
| <b>Head Style:</b>                                    | Flat Countersunk                                                                                                                     |
| <b>Head Diameter:</b>                                 | 0.328 Inches Minimum And 0.385 Inches Maximum                                                                                        |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                                                                                      |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                                                                                                        |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches                                                                                                                         |
| <b>Grip Length:</b>                                   | 1.865 Inches Minimum And 1.885 Inches Maximum                                                                                        |
| <b>Thread Quantity Per Inch:</b>                      | 32                                                                                                                                   |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch                                                                                                        |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall                                                                  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                                                                       |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                                                                                                                |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                                                                                             |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall                                                                                                                      |
| <b>Surface Treatment Document And Classification:</b> | Nas672 Assn Std Single Treatment Response Overall                                                                                    |
| <b>Thread Series Designator:</b>                      | Unf                                                                                                                                  |
| <b>Specification/standard Data:</b>                   | 80205-nas2803 Professional/industrial Association Standard                                                                           |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS2803-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.