

Description

Fastener Length: 1-19/32", Thread: 3/8-24, Thread Length: 15/32",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS2816C18D
Minimum Qty (MOQ):	1
NSN:	5306-01-583-0236
Schedule B:	7318.15.8085
ECCN:	EAR99

NAS2816C18D



P/N NAS2816C18D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.429 Inches Minimum And 0.479 Inches Maximum
Fastener Length:	1.564 Inches Minimum And 1.594 Inches Maximum
Head Style:	Dished Hexagon
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	171000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2816C18D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.