

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 5/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2833C5PT
Minimum Qty (MOQ):	10
NSN:	5305-01-549-3833
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS2833C5PT Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.655 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.377 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Nas 4006 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2833C5PT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.