

## Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 5/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS2833C5PT
Minimum Qty (MOQ):	10
NSN:	5305-01-549-3833
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N NAS2833C5PT Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.655 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.377 Inches Minimum And 0.385 Inches Maximum
<b>Grip Diameter:</b>	0.188 Inches Minimum And 0.189 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Nas 4006 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2833C5PT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.